




**Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Paint
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Maston Oy
Teollisuustie 10
FI 02880 Veikkola - Finland
Phone.: +358 20 7188 580
maston@maston.fi
www.maston.fi
- 1.4 Emergency telephone number:** Myrkytystietokeskus (Giftinformationcentralen) PL 340 00029 HUS FINLAND +358(0)9471977

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aerosol 1: Pressurised container: May burst if heated., H229
Aerosol 1: Flammable aerosols, Category 1, H222
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger

Hazard statements:
Aerosol 1: H229 - Pressurised container: May burst if heated
Aerosol 1: H222 - Extremely flammable aerosol
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
Eye Irrit. 2: H319 - Causes serious eye irritation
Skin Irrit. 2: H315 - Causes skin irritation
STOT SE 3: H336 - May cause drowsiness or dizziness
Precautionary statements:
P102: Keep out of reach of children
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211: Do not spray on an open flame or other ignition source
P251: Do not pierce or burn, even after use
P260: Do not breathe spray
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
Substances that contribute to the classification
Butanone (CAS: 78-93-3); Ethyl acetate (CAS: 141-78-6); Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS: 64742-49-0);
Butan-2-ol (CAS: 78-92-2)
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria
DK. Mal code: 3-1

** Changes with regards to the previous version

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **
3.1 Substance:

Non-applicable

3.2 Mixture:
Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	dimethyl ether⁽¹⁾ ATP CLP00 Regulation 1272/2008 Flam. Gas 1A: H220; Press. Gas: H280 - Danger	30 - <50 %
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	Butanone⁽¹⁾ ATP CLP00 Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	10 - <20 %
CAS: 64742-49-0 EC: 265-151-9 Index: 649-328-00-1 REACH: 01-2119475133-43-XXXX	Naphtha (petroleum), hydrotreated light, < 0.1 % EC 200-753-7⁽¹⁾ ATP ATP01 Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225 - Danger	5 - <10 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Xylene⁽¹⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	5 - <10 %
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX	Ethyl acetate⁽¹⁾ ATP CLP00 Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	5 - <10 %
CAS: 64742-49-0 EC: 927-510-4 Index: Non-applicable REACH: 01-2119475515-33-XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics⁽²⁾ Self-classified Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	2,5 - <5 %
CAS: 78-92-2 EC: 201-158-5 Index: 603-004-01-3 REACH: 01-2119475146-36-XXXX	Butan-2-ol⁽¹⁾ ATP CLP00 Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336 - Warning	1 - <2,5 %
CAS: Non-applicable EC: 921-024-6 Index: Non-applicable REACH: 01-2119475514-35-XXXX	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane⁽²⁾ Self-classified Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	1 - <2,5 %
CAS: Non-applicable EC: 920-750-0 Index: Non-applicable REACH: 01-2119473851-33-XXXX	Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclics⁽²⁾ Self-classified Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	1 - <2,5 %
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24-XXXX	Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7⁽¹⁾ ATP ATP01 Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336; EUH066 - Danger	0,25 - <1 %
CAS: 78-83-1 EC: 201-148-0 Index: 603-108-00-1 REACH: 01-2119484609-23-XXXX	2-methylpropan-1-ol⁽¹⁾ ATP CLP00 Regulation 1272/2008 Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	0,25 - <1 %
CAS: 108-83-8 EC: 203-620-1 Index: 606-005-00-X REACH: 01-2119474441-41-XXXX	2,6-dimethylheptan-4-one⁽¹⁾ ATP CLP00 Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H335 - Warning	0,25 - <1 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Identification	Specific concentration limit
2,6-dimethylheptan-4-one CAS: 108-83-8 EC: 203-620-1	% (w/w) >=10: STOT SE 3 - H335

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

- CONTINUED ON NEXT PAGE -



Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 50 °C
Maximum time: 60 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Occupational exposure limits	
	IOELV (8h)	IOELV (STEL)
dimethyl ether CAS: 115-10-6 EC: 204-065-8	1000 ppm	1920 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm
	IOELV (STEL)	221 mg/m ³
Butanone	IOELV (8h)	100 ppm
		442 mg/m ³
	IOELV (8h)	200 ppm
		600 mg/m ³

- CONTINUED ON NEXT PAGE -

Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Occupational exposure limits		
CAS: 78-93-3	EC: 201-159-0	IOELV (STEL)	300 ppm	900 mg/m ³
Ethyl acetate		IOELV (8h)	200 ppm	734 mg/m ³
CAS: 141-78-6	EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1894 mg/m ³	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m ³	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS: 64742-49-0 EC: 927-510-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2085 mg/m ³	Non-applicable
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	405 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	212 mg/m ³	Non-applicable
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable EC: 921-024-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	773 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2035 mg/m ³	Non-applicable
Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclics CAS: Non-applicable EC: 920-750-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	773 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2035 mg/m ³	Non-applicable
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m ³
2,6-dimethylheptan-4-one CAS: 108-83-8 EC: 203-620-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	80 mg/kg	Non-applicable
	Inhalation	290 mg/m ³	290 mg/m ³	479 mg/m ³	290 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	471 mg/m ³	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	106 mg/m ³	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m ³	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³

- CONTINUED ON NEXT PAGE -

Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS: 64742-49-0 EC: 927-510-4	Oral	Non-applicable	Non-applicable	149 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	149 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	447 mg/m ³	Non-applicable
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	203 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	52 mg/m ³	Non-applicable
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable EC: 921-024-6	Oral	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	608 mg/m ³	Non-applicable
Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics CAS: Non-applicable EC: 920-750-0	Oral	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	608 mg/m ³	Non-applicable
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	55 mg/m ³
2,6-dimethylheptan-4-one CAS: 108-83-8 EC: 203-620-1	Oral	Non-applicable	Non-applicable	7,14 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	28,5 mg/kg	Non-applicable
	Inhalation	145 mg/m ³	145 mg/m ³	171 mg/m ³	145 mg/m ³

PNEC:

Identification				
dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	160 mg/L	Fresh water	0,155 mg/L
	Soil	0,045 mg/kg	Marine water	0,016 mg/L
	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,069 mg/kg
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55,8 mg/L
	Soil	22,5 mg/kg	Marine water	55,8 mg/L
	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1000 g/kg	Sediment (Marine water)	284,7 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	STP	650 mg/L	Fresh water	0,24 mg/L
	Soil	0,148 mg/kg	Marine water	0,024 mg/L
	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	200 g/kg	Sediment (Marine water)	0,115 mg/kg
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	STP	761 mg/L	Fresh water	47,1 mg/L
	Soil	11,58 mg/kg	Marine water	47,1 mg/L
	Intermittent	47,1 mg/L	Sediment (Fresh water)	196,19 mg/kg
	Oral	1000 g/kg	Sediment (Marine water)	196,19 mg/kg
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	STP	10 mg/L	Fresh water	0,4 mg/L
	Soil	0,0699 mg/kg	Marine water	0,04 mg/L
	Intermittent	11 mg/L	Sediment (Fresh water)	1,52 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,152 mg/kg
2,6-dimethylheptan-4-one CAS: 108-83-8 EC: 203-620-1	STP	2,55 mg/L	Fresh water	0,03 mg/L
	Soil	0,0746 mg/kg	Marine water	0,003 mg/L
	Intermittent	0,3 mg/L	Sediment (Fresh water)	0,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,046 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

- CONTINUED ON NEXT PAGE -



Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Non-applicable

D.- Ocular and facial protection

Non-applicable

E.- Body protection

Non-applicable

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	76,08 % weight
V.O.C. density at 20 °C:	613,24 kg/m ³ (613,24 g/L)
Average carbon number:	5,86
Average molecular weight:	91,7 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Aerosol
Appearance:	Not available
Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	-25 - 168 °C (Propellant)
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	806 kg/m ³
Relative density at 20 °C:	0,806
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Recipient pressure:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

Flammability:

Flash Point:	-41 °C (Propellant)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	240 °C (Propellant)
Lower flammability limit:	0,8 % Volume
Upper flammability limit:	12 % Volume

Explosive:

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

** Changes with regards to the previous version

Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805
SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Identification	Acute toxicity		Genus
	LD50	LC50	
Naphtha (petroleum), hydrotreated light , < 0.1 % EC 200-753-7 CAS: 64742-49-0 EC: 265-151-9	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	12 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23,5 mg/L (4 h)	Rat
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable EC: 921-024-6	LD50 oral	5840 mg/kg	Rat
	LD50 dermal	2920 mg/kg	Rat
	LC50 inhalation	Non-applicable	
dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	308,5 mg/L (4 h)	Rat
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	LD50 oral	3350 mg/kg	Rat
	LD50 dermal	2460 mg/kg	Rabbit
	LC50 inhalation	24,6 mg/L (4 h)	Rat

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
Butanone CAS: 78-93-3 EC: 201-159-0	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
Naphtha (petroleum), hydrotreated light , < 0.1 % EC 200-753-7 CAS: 64742-49-0 EC: 265-151-9	LC50	Non-applicable		
	EC50	4.3 mg/L (96 h)	Crangon crangon	Crustacean
	EC50	Non-applicable		
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS: 64742-49-0 EC: 927-510-4	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	LC50	3670 mg/L (96 h)	Pimephales promelas	Fish
	EC50	3750 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	95 mg/L (168 h)	Scenedesmus quadricauda	Algae

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805**

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Acute toxicity		Species	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable EC: 921-024-6	LC50	5.1 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		
Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics CAS: Non-applicable EC: 920-750-0	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Algae
2,6-dimethylheptan-4-one CAS: 108-83-8 EC: 203-620-1	LC50	140 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	250 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	100 mg/L (96 h)	Selenastrum capricornutum	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2.03 g O2/g	Concentration	Non-applicable
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BOD5	1.36 g O2/g	Concentration	100 mg/L
	COD	1.69 g O2/g	Period	14 days
	BOD5/COD	0.81	% Biodegradable	83 %
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS: 64742-49-0 EC: 927-510-4	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	95 %
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	BOD5	0.0015 g O2/g	Concentration	100 mg/L
	COD	0.002 g O2/g	Period	14 days
	BOD5/COD	0.76	% Biodegradable	73,5 %
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS: Non-applicable EC: 921-024-6	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	98 %
Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics CAS: Non-applicable EC: 920-750-0	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	98 %
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BOD5	0.19 g O2/g	Concentration	Non-applicable
	COD	0.44 g O2/g	Period	Non-applicable
	BOD5/COD	0.43	% Biodegradable	Non-applicable
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	BOD5	0.4 g O2/g	Concentration	100 mg/L
	COD	2.41 g O2/g	Period	14 days
	BOD5/COD	0.17	% Biodegradable	90 %
2,6-dimethylheptan-4-one CAS: 108-83-8 EC: 203-620-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	20 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %

12.3 Bioaccumulative potential:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805
SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Bioaccumulation potential	
Butanone CAS: 78-93-3 EC: 201-159-0	BCF	3
	Pow Log	0.29
	Potential	Low
Naphtha (petroleum), hydrotreated light , < 0.1 % EC 200-753-7 CAS: 64742-49-0 EC: 265-151-9	BCF	380
	Pow Log	3.7
	Potential	High
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BCF	30
	Pow Log	0.73
	Potential	Moderate
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	BCF	3
	Pow Log	0.61
	Potential	Low
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BCF	
	Pow Log	4
	Potential	
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	BCF	3
	Pow Log	0.76
	Potential	Low
2,6-dimethylheptan-4-one CAS: 108-83-8 EC: 203-620-1	BCF	7
	Pow Log	2.56
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
dimethyl ether CAS: 115-10-6 EC: 204-065-8	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1,136E-2 N/m (25 °C)	Moist soil	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5,77 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Koc	59	Henry	13,58 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,433E-2 N/m (25 °C)	Moist soil	Non-applicable
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,378E-2 N/m (25 °C)	Moist soil	Non-applicable
2,6-dimethylheptan-4-one CAS: 108-83-8 EC: 203-620-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,28E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: 190, 327, 344, 625
 Tunnel restriction code: D
 Physico-Chemical properties: see section 9
 Limited quantities: 1 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: 63, 959, 190, 277, 327, 344
 EmS Codes: F-D, S-U
 Physico-Chemical properties: see section 9
 Limited quantities: 1 L
 Segregation group: Non-applicable
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2020:

- CONTINUED ON NEXT PAGE -

Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number:	UN1950
14.2 UN proper shipping name:	AEROSOLS, flammable
14.3 Transport hazard class(es):	2
Labels:	2.1
14.4 Packing group:	N/A
14.5 Environmental hazards:	No
14.6 Special precautions for user	
Physico-Chemical properties:	see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Non-applicable
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a		150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
 - Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics
 - Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements
- Supplementary information

Texts of the legislative phrases mentioned in section 2:

- CONTINUED ON NEXT PAGE -



Maston - Spray Seal - various colors
1970121, 1970221, 1970800, 1970805

SECTION 16: OTHER INFORMATION (continued)

H336: May cause drowsiness or dizziness
H412: Harmful to aquatic life with long lasting effects
H315: Causes skin irritation
H229: Pressurised container: May burst if heated
H222: Extremely flammable aerosol
H319: Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
Eye Dam. 1: H318 - Causes serious eye damage
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Gas 1A: H220 - Extremely flammable gas
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Press. Gas: H280 - Contains gas under pressure, may explode if heated
Skin Irrit. 2: H315 - Causes skin irritation
STOT SE 3: H335 - May cause respiratory irritation
STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

STOT SE 3: Calculation method
Aquatic Chronic 3: Calculation method
Skin Irrit. 2: Calculation method
Aerosol 1: Calculation method
Aerosol 1: Calculation method
Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -